

**SIRIUS ENERGY STORAGE MODULE
TECHNICAL DATA SHEET**

Part Number: 10000-384-A-1C-TM-SD-A-X-DC-G | Version Date: July 2020



PERFORMANCE SPECIFICATIONS	Voltage (Nominal)	384 V _{dc}
	Maximum Charge Voltage	432 V _{dc}
	Discharge Cut-Off Voltage	367 V _{dc}
	Total Energy	10000 WH @ 1C
	Maximum Charge Rate	130 A (5C)
	Maximum Discharge Rate	130 A (5C)
	Recommended Charge Rate	26 A (1C)
	Recommended Discharge Rate	52 A (2C)
ENVIRONMENTAL SPECIFICATIONS	Cell Operating Temperature ¹	-30 °C to 80 °C
	Operating Humidity	Non-Condensing

This technical data sheet may change without notice and at the sole discretion of Kilowatt Labs, Inc.

Solutions for: Microgrids | C&I and Residential Solar | Electric Vehicles | Utility Grade Storage

Kilowatt Labs, Inc. | www.kilowattlabs.com

**SIRIUS ENERGY STORAGE MODULE
TECHNICAL DATA SHEET**

Part Number: 10000-384-A-1C-TM-SD-A-X-DC-G | Version Date: July 2020

MECHANICAL SPECIFICATIONS	Dimensions (w × d × h) mm	567 x 640 x 1089
	Weight (Kg)	277
	Module Casing Material	GI Powdered
	Terminal Type	HVIL 150A-S-1S
SMART FEATURES	Monitoring Data	Total Cell Voltage, Current, Temperatures, SOC and Energy
	Remote Monitoring	Via Sirius View App
	Communication and Connectivity	USB Port
	Alarm	Audible alarm in the event of Over/under-Voltage, Over-Current, Over Temperature
	Dry Contacts × 2	DIN Connector (Programmable ⁷)
SIRIUSVIEW SOFTWARE	Module Monitoring	Current, maximum and minimum Voltage, Temperature, Total Energy delivered, SOC, Graphs
	System Monitoring	Modules Monitoring (connected in parallel or series)
MODULE SERVICE LIFE	Projected Cycle Life ^{2,3}	1 million cycles
	Projected Calendar Life ^{3,4}	45 years
	Shelf Life ⁵	10 years
	Warehousing	Can be stored at any SOC without affecting cycle life
SAFETY PERFORMANCE	Over Voltage	Hardware protection, Charging disconnection
	Under Voltage	Hardware protection, Module shut down
	Over Current	Hardware protection, Module shut down
	Over temperature	Hardware protection, Module shut down
	Additional Safety	2× 125A 2P DC circuit breakers + 10A DC circuit breaker +2 DC contactors protection
COMPLIANCE⁶ INFORMATION	EN55032:2015, EN55024:2010, EN61000-4-2:2009, EN61000 EN61000:2008+A2:2010	
PRECAUTIONS	Alarm	In case of alarm, immediately rectify/attend to the cause of the alarm.
	Physical Damage	In case the Module is physically damaged due to any event, do not install and energize the Module under any circumstances and contact your Reseller.

**SIRIUS ENERGY STORAGE MODULE
TECHNICAL DATA SHEET**

Part Number: 10000-384-A-1C-TM-SD-A-X-DC-G | Version Date: July 2020

Short Circuit	Ensure precautions to prevent short-circuit under all circumstances.
Galvanic isolation	When connecting to external devices ensure that galvanic isolation does not exceed 1000V.
Charge Current	Under no circumstances must the charge current exceed 26A.
Discharge Current	Under no circumstances must the discharge current exceed 52A.
Charging Voltage	Under no circumstances must the charging voltage exceed 432 V _{dc} for more than 60 seconds.
Charge Cycle	During charge cycle ensure never to exceed constant voltage of 432 V _{dc} and constant current of 26A.
Series Connection	Series connection is not allowed.
Parallel Connection	There is no limit on the number of Modules that can be connected in parallel.
Series-Parallel Connection	Modules cannot be connected in Series-Parallel combination under any circumstance.

¹The temperature range indicates the range in which the supercapacitor cells can operate. The performance of the cells may vary if they are continuously operated outside a temperature range of -10°C to 55°C, and/or at C-rates higher than the maximum charge/discharge rate specified in this spec sheet. The operating temperature range of the Module varies based on the application. If the Module is to be operated continuously outside a temperature range of -10°C to 55°C, and/or at C-rates higher than the maximum charge/discharge rate specified in the spec sheet, please consult Kilowatt Labs or its Reseller prior to deploying.

²Projected life of supercapacitor cells. Cycle life will vary if cycled more than 4 times a day.

³Additional terms and conditions, including a limited warranty, will apply at the time of purchase.

⁴Projected Calendar life of supercapacitor cells from the date of first operation.

⁵Shelf life is the life of the Module (in years) from the date it is manufactured to the time it is first operated.

⁶CE certification is completed for supercapacitor cells.

⁷Programmable features can be activated to program for appropriate version of Sirius View software.

Product dimensions are for reference only unless otherwise identified and may change without notice.

For critical applications, please contact your Reseller.